

MINUTEMAN Pro500e

Thursday, 15 February 2007

Description:

The MINUTEMAN® PRO500E is a 500VA/350W 120 VAC line-interactive UPS with 4 battery backup/surge outlets, 2 surge-only outlets, USB and RS232 communication ports, MINUTEMAN SentryII®; power management software and diagnostic software, and RJ45/RJ11 network/modem surge protection.

Back-up time - full load: 6.5 minutes

Back-up time - half load: 17.2 minutes

Features:

- The built-in double-boost and single-buck AVR (Automatic Voltage Regulator) function compensates for broader range of low AC voltage situations like brownouts and sags as well as high AC voltage situations like surges and spikes saving internal battery power for blackouts and extending the life of the batteries
- Independent Battery Bypass®; allows the UPS to provide voltage regulation with surge and spike protection on utility AC power even when batteries are weak or dead
- Includes MINUTEMAN SentryII®; power management and diagnostic software to provide added control and allow unattended PC shutdown (for use on individual PCs or multiple workstations on networks)
- Integrated USB and RS232 ports for software communications (USB and RS232 cables included)
- 3-Year Parts and Labor Warranty
- \$50,000 MINUTEMAN Platinum Protection Plan® (U.S. and Canada)

Properties:

Device type: Uninterruptible Power Supply

Input plug type: NEMA 5-15P

Input voltage: 120

Output voltage: 120

Number of fully protected outlets: 4 (NEMA 5-15R)

Number of surge protected only outlets: 2 (NEMA 5-15R)

Phone / modem (RJ-11) protection? Yes

Network (RJ-45) protection? Yes

No. of serial (DB-9) ports: 1

No. of dry contact ports: 0

USB port: Yes

Battery:

User replaceable battery? Yes

No. of internal batteries: 1

Replacement battery description: 12 Volt 9 Amp Hour

Replacement battery part no.: 37000025

Technical Attributes:

SNMP manageable? Yes

Power in Watts: 350

EMI/RFI filtering? Yes

Max. energy dissipation: 500 (Joules)

Protected equipment insurance value: \$50000 USD (US and Canada Only)

Switchover time: 2-6 ms

Software:

*Operating system shutdown software included: Yes

Op. System(s) supported by SentryII software: Microsoft Windows 95/98/ME/NT4/XP/2000/2003 (SP6 recommended for Windows NT 4.0), Novell NetWare 4.11 and 5.1, Red Hat Linux (versions 6.12, 7.1, and 9.0), SCO UnixWare version 7.1.1, SCO Open Server version 5.06, HP-UX version 11, IBM AIX version 4, and other Unix/Linux systems

Product Dimensions (in inches) :

Length: 6.38
Width/Depth: 12.56
Height: 7.56
Weight: 20.30 lbs.