

## MINUTEMAN E 750

Thursday, 15 February 2007

### Description:

The MINUTEMAN Enterprise E 750 is a 750VA/450W 120 VAC true sinewave, extended runtime UPS designed for desktop, tower, wall, or 2U high rackmount (19 or 23 inches) configurations. 23 inch rack or wallmount installations require the optional rack and wall kit.

Back-up time - full load: 11.5 minutes

Back-up time - half load: 27.6 minutes

### Features:

- True Sinewave Output
- Scalable Unlimited Runtime via External Battery Packs with Independent Chargers
- Universal Design for Desktop, Tower, Rackmount, and Wallmount Installation (For mounting on a wall, see optional Wallmount Kit)
- Includes standard 19 inch rack hardware and tower mounting feet (For mounting in a 23 inch rack, see optional 2U 23-inch Rack Kit)
- Space-saving 16 inches (41 centimeter) Depth
- Full Protection from Sags, Surges, Spikes & Blackouts
- Voltage Regulation Incorporating Double Boost and Double Buck
- Optional SNMP Card for Remote Power Management (SNMP or Web browser)
- Includes MINUTEMAN SentryII &trade; Power Management Software CD and Communications Cable
- Fax/Modem/Data Protection Slots
- Front-Access, Hot Swappable Batteries
- Industry Leading 3-Year Warranty

### Properties:

Device type: Uninterruptible Power Supply

Input plug type: NEMA 5-15P

Input voltage: 120

Output voltage: 120

Number of fully protected outlets: 3 (NEMA 5-15R)

Number of surge protected only outlets: 1 (NEMA 5-15R)

Phone / modem (RJ-11) protection? Yes

Network (RJ-45) protection? Yes

No. of serial (DB-9) ports: 1

No. of dry contact ports: 0

USB port: No

### Battery:

User replaceable battery? Yes

No. of internal batteries: 2

Replacement battery description: 12 Volt DC 7.2 Amp Hour

Replacement battery part no.: 37000007

### Technical Attributes:

SNMP manageable? Yes

Power in Watts: 450

EMI/RFI filtering? Yes

Max. energy dissipation: 508 (Joules)

Protected equipment insurance value: \$40000 USD (US and Canada Only)

Switchover time: 2 ms max

### Software:

\*Operating system shutdown software included: Yes

Op. System(s) supported by SentryII software: Microsoft Windows 95/98/ME/NT4/XP/2000/2003 (SP6 recommended for Windows NT 4.0), Novell NetWare 4.11 and 5.1, Red Hat Linux (versions 6.12, 7.1, and 9.0), SCO UnixWare version 7.1.1, SCO Open Server version 5.06, HP-UX version 11, IBM AIX version 4, and other Unix/Linux systems

Product Dimensions (in inches) :

Length: 17.00

Width/Depth: 16.00

Height: 3.50

Weight: 51.70 lbs.